# **CEE-BEE CLEANER A-883**

by Cee-Bee®



# data sheet

**CEE-BEE CLEANER A-883** is a highly concentrated, non-solvent gel specifically designed to clean aircraft exterior surfaces. Also for degreasing engine exteriors prior to tear-down.

#### **BENEFITS**

- 1. Very effectively penetrates and removes heavy greasy soils.
- 2. Clings to vertical and overhead surfaces.
- 3. Rinses off easily without streaking, even after drying on the surface.
- 4. Safe on high strength steel, aluminum, magnesium, titanium and other common aircraft structural metals, good quality paints and acrylic plastics.
- 5. Does not contain any material considered toxic by state or federal regulations.
- 6. Won't stain after dwell time. Has a pleasant, non-offensive odor.
- 7. Environmentally friendly, surfactants biodegradable.
- 8. Non-flammable.

#### **CONFORMS TO**

- MIL-PRF-87937D, TYPE III (QPL)
- EPA 796.3100: AEROBIC AQUATIC BIODEGRADATION

NOTE: To place an order, call or FAX Customer Service at 800-327-0466 / FAX 1-216-441-1377
Cee-Bee Cleaner A-883 Product Code # 20113





### NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be understood. If you have any questions, pllease contact your McGean-Rohco representative before proceeding.

### **USE PROCEDURES**

**Heavy greasy soils:** Use undiluted. Will cling to vertical and overhead

surfaces for maximum cleaning action.

**Moderate to heavy soils:** Mix 1 part cleaner with 2 to 10 parts water.

**Light to moderate soils**: Mix 1 part cleaner with 10 to 20 parts water.

# With water rinse

1. Apply cleaner with mops, brushes or non-atomizing spray. Start at the bottom of the surface to be cleaned and work upward to avoid streaking.

- 2. Allow cleaner to dwell at least 5 minutes until soils are penetrated, then agitate surface with a brush or mop.
- 3. Rinse thoroughly with high pressure water, starting at the top and working downward.

The more concentrated cleaner solutions will require additional rinsing to avoid streaking and filming.

#### Without water rinse

- 1. Wipe the surface with rags or mops saturated with cleaner solution to loosen the soils.
- 2. Remove loosened soils with clean, dry rags or mops, turning frequently to avoid re-deposition of soils.

## Spray-on Cleaning and Degreasing Engine Exteriors

- 1. Mask all openings to the engine interior (the inlet, exhaust, fuel and oil lines left open, bleeders, breather tubes and open electrical connectors.)
- 2. Spray, steam, or foam on Cee-Bee A-883 Cleaner. Allow to dwell 10 to 20 minutes.
- 3. Flush with warm or hot water.

# **PROPERTIES**

- Blue gel with a pleasant odor.
- No flash point.

# **PRECAUTIONS**

- Irritating to eyes and skin. Avoid contact. Rubber gloves and chemical goggles or face shields are recommended. Some form of eye protection is always absolutely essential.
- In case of accidental contact with eyes or skin, flush thoroughly with water. If irritation persists, seek medical attention.
- Do not take internally.

Copyright 1996 McGean-Rohco, Inc. Rev. 2/05