

CEE-BEE REMOVER J-91

by Cee-Bee®



d a t a s h e e t

CEE-BEE REMOVER J-91 is a diphasic, highly active, cold paint, dry film lubricant, and resistant coatings remover.

BENEFITS

- Extremely active on tough cured epoxy paint systems.
- Contains an oil seal to control moisture pickup.
- Safe on stainless steel, aluminum and titanium when used as directed.
- Does not contain organic solvents or phenolics.

CONFORMS TO

- **ROLLS ROYCE OMAT NO. 1/56B**

**NOTE: To place an order, call or FAX Customer Service at
800-327-0466 / FAX 1-216-441-1377
Cee-Bee Remover J-91 Product Code # 26049**



NOTES PRIOR TO HANDLING

Before using your McGean-Rohco, Inc. products, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean-Rohco representative before proceeding.

USE PROCEDURES

1. Carefully charge tank with Cee-Bee J-91 as received. Use at ambient temperature.
2. Totally immerse components to be stripped into the lower, acidic layer. The required immersion time will vary. 30 to 60 minutes is average.
3. After cleaning is complete, remove the parts from the bath and allow to drain over the tank.
4. Immediately dip rinse the parts in cold running water.
5. Rinse with high pressure water followed by a neutralizing alkaline dip.
6. A final dip rinse is recommended.

CAUTION! Rinse tanks should be arranged so that water CANNOT enter the Cee-Bee J-91 bath!

CONTROL

- Use rigid high density polyethylene or polypropylene tanks, or steel tanks lined with these materials for containing Cee-Bee J-91.
- Maintain an approximately 4" oil seal to prevent moisture from entering the lower acidic layer. The seal can be replenished by additions of Cee-Bee J-91 Additive O.

PROPERTIES

- A brown diphase liquid.

PRECAUTIONS

- **WARNING! DANGER! Contains concentrated sulfuric acid.** Corrosive. Do not allow any contact with eyes, skin or clothing. May cause burns or external ulcers. Do not take internally. Do not breathe any fumes, mist or vapor. Use with adequate ventilation. Wash thoroughly after handling. Wear OSHA-approved acid resistant gloves, full face shield, or proper OSHA-approved respirator fitted with proper acid filter cartridge. Wear proper protective clothing sufficient to prevent any skin contact.
- In case of accidental contact with eyes. Flush with water for at least 15 minutes. Obtain prompt medical attention. For skin contact, flush with water for at least 15 minutes. If irritation persists, seek prompt medical attention.
- For inhalation, remove to fresh air.
- For ingestion, do NOT induce vomiting. Administer large quantities of water and immediately obtain medical attention.
- Wash clothing before reuse.
- **WARNING!** Bath may become corrosive to metals if contaminated with water.