

CHROMIUM TARTRATE SOLUTION

FORMULA: $Cr_2(C_4H_4O_6)_3$ in Water

SPECIFICATIONS: Trivalent Chrome Cr (III) 4.0 - 5.0%

Hexavalent Chrome Cr (VI) None Detected

<0.0001%

Specific Gravity 1.5 Typical

FORM: Dark Reddish-Purple Solution

STANDARD PACKAGE: 500 pound drum, 45 pound pail

APPLICATIONS: Chrome Tartrate is used as mordants in textile

dyeing, chrome conversion coatings, hydrogenation catalysts and anti-foulants for oil field applications.

35222 CAS 62498-20-8 BJP/MFG 04/01/14

BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE SAFETY AND HAZARD INFORMATION CONTAINED IN OUR MATERIAL SAFETY DATA SHEETS. McGean (the Seller) presents the information without warranty and disclaims any liability arising from its use and misuse. Seller recommends use of the information and Seller's products solely in commercial processes which are specified by Seller and which do not violate any third-party patent rights or any laws or regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.