

# CEE-BEE A-276LV REMOVER

by Cee-Bee®



## d a t a s h e e t

**CEE-BEE A-276LV REMOVER** is a viscous, low voc alkaline liquid used for removing temporary protective coatings from painted surfaces, bare metal and plastics.

### BENEFITS

- Rapid and complete coating removal.
- Thixotropic. Clings to vertical and inclined surfaces.
- Safe on all common aircraft structural metals, including high strength steel, stainless steel, mild steel, aluminum, magnesium and titanium.
- Will not damage good quality lacquer or paint, acrylic plastics, rubber, neoprene, glass or ceramics.
- Contains no materials that require reporting by EPA under Section 313 of Title III of SARA.
- Non-flammable. No flash point.

### CONFORMS TO

- **BMS 15-12 REV. K (QPL)**
- **BOEING BAC 5034-1**
- **DOUGLAS DPM 5901-3**
- **T.O.1-1-691**

**NOTE: To place an order, call or FAX Customer Service at  
800-932-7006 / (FAX) 216-441-1377  
Cee-Bee A-276LV Remover – Product Code #21009**



## NOTES PRIOR TO HANDLING

Before using any McGean product, all safety and operating instructions should be read and understood. If you have any questions, please contact your McGean representative before proceeding.

## USE PROCEDURES

1. Cool surface with a light spray of water if temperature exceeds 100°F. Use Cee-Bee A-276LV undiluted and apply with non-atomizing spray equipment, mops, brushes or rollers.
2. Allow a dwell time sufficient to penetrate and loosen the coating. If required, agitate lightly with a mop or brush.
3. Rinse thoroughly with flowing water.

## PROPERTIES

- Yellow, viscous liquid. No flash point.

## PRECAUTIONS

- Avoid eye and skin contact. Use rubber gloves and face shield or goggles. Use with adequate ventilation.
- Do not take internally. For contact, flush well with water. If eye irritation persists, seek medical attention.