



BASIC CHROMIC SULFATE SOLUTION

FORMULA:	Cr(OH)SO₄ In Water		
TYPICAL ANALYSIS:	Trivalent Chrome	Cr(III)	11.6 – 12.4%
	Basicity*		30% - 36%
	Chloride	Cl	0.01% maximum
	Iron	Fe	0.01% maximum
	Copper	Cu	0.01% maximum
	Hexavalent Chrome	Cr (VI)	None Detected <0.0001%
FORM:	Dark Green Solution		
STANDARD PACKAGE:	650 pound drum; 4 per pallet 60 pound plastic pail; 24 per pallet		
APPLICATIONS:	Uses for Basic Chromic Sulfates include metal finishing, pigments, textile mordants, leather tanning, and catalysts.		
*Basicity	Percent of charge on chrome displaced by hydroxyl ion		

35434
CAS# 12336-95-7
BJP/MFG
04/01/14

BEFORE USING ANY OF THESE PRODUCTS, YOU MUST BECOME COMPLETELY FAMILIAR WITH THE SAFETY AND HAZARD INFORMATION CONTAINED IN OUR MATERIAL SAFETY DATA SHEETS. McGean (the Seller) presents the information without warranty and disclaims any liability arising from its use and misuse. Seller recommends use of the information and Seller's products solely in commercial processes which are specified by Seller and which do not violate any third-party patent rights or any laws or regulations. THE SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE EXCEPT AS EXPRESSLY STATED IN THE SELLER'S SALES CONTRACT OR SALES ACKNOWLEDGEMENT FORM.